



Version aft master cabin

## GENERAL SPECIFICATIONS

• L.O.A	17.80 m
• Length of hull	17.20 m
• L.W.L.	15.00 m
• Width of hull	4.93 m
• Long draught (min)	2.60 m
• Short draught (min)	2.10 m
• Air draught (max)	23.40 m
• Light displacement EC	22 055 kg
• Fuel tank capacity	480 l (+ 185 l Optional extra)
• Freshwater capacity	1 000 l
• Engine power	110 HP - 160 HP

## ARCHITECTS / DESIGNERS

• Architect Naval	Far Yacht Design
• Styling	AB Concept / Franck Darnet Design

## EC CERTIFICATE

• Category A	10 persons
• Category B	11 persons
• Category C	14 persons

## STANDARD SAIL LAYOUT AND AREA

• Mainsail	74.00 m <sup>2</sup>
• Genoa	94.00 m <sup>2</sup>
• Spinnaker	220.00 m <sup>2</sup>
• I	20.00 m
• J	6.53 m
• P	19.10 m
• E	6.87 m
• SL	20.00 m
• SMW	11.70 m

## STANDARD EQUIPMENT

### CONSTRUCTION

Design made following European Directive requirements and according to EC certification.

- Monolithic design hull (Polyester-reinforced fibreglass)
- Monolithic structural counter moulding laminated and stuck to hull
- Fibreglass and balsa wood sandwich deck, covered with " diamond-tip " type non-slip surface
- Stainless steel protective banding each side of the hull
- Deck hull join screwed, stuck and banded with 1 solid wood bulwark
- Cast iron keel fixed with bolts and stainless steel veneer and stuck
- Underhung rudder with compound stock and stainless steel bearing collars
- White coloured hull - Blue and Gold hull decoration

### DECK EQUIPMENT

#### RIGGING

- Classical mast 9/10st - aluminium anodised - fitted to keel - 3 Cross tree levels
- 2 Retractable steps
- Deck partner fitting with swivel blocks
- Mainsail luff track - without bearing traveller
- Boom in anodised aluminium
- Discontinuous stainless steel single strand standing rigging - Stainless steel stay bolt plate taken up on bow - Shroud bolt plates, taken up by stainless steel tie rods on the structural counter moulding - Stainless steel backstay bolt plates on transom
- Backstay double
- Fixed boom kicking strap
- Genoa furler manual - Drum on deck
- Mainsail sheet track
- 2 Genoa sheet tracks - 2 Genoa car sliders - 2 Single bearing blocks for genoa sheet leads
- Running rigging: 1 Genoa halyard - 1 Main halyard - 1 Boom topping lift - 3 reef lines - 1 Mainsail foot - 2 Genoa sheets - 1 Main sheet - 2 Mainsail traveller pass controls
- 2 cheek blocks 6 Sheaves
- 8 Clutches
- 1 Halyard rack at mast foot
- Pre-fitted for spinnaker (6 stirrup bolt plates and clutches)
- 4 Flexible vent stems, mounted on dorade boxes
- Wind indicator WINDEX

#### WINCHES

Winches Harken

- 2 Primary genoa sheet winches (H70.2 STC)
- 1 Electrical rigging winch To starboard (H46.2 STCE)
- 1 Port rigging winch (H46.2 STC)
- 2 Winch handles
- 2 Winch handle boxes in the rope locker

#### MOORING - ANCHORING

- Self-bailing chain locker - 2 Access hatches
- 1 Stainless steel bow fitting
- Double bow roller
- Vertical electric windlass 2000 W - Fitted onto deck - Remote control
- 8 Stainless steel mooring cleats, (2 forward - 4 amidships - 2 aft)
- Bow thruster - Control at steering station

#### SAIL LOCKER

- Access through lockable deck hatch
- Companionway ladder in stainless steel
- Shelves along inside of hull

#### PERSONNEL GUARDS

- Stainless steel pulpit Open - solid wood steps
- Stainless steel pushpit
- Double guardrails - Stainless steel stanchions
- Side opening in port and starboard guardrails
- 1 Ring lifebuoy bracket
- 1 Outboard engine bracket
- Removable solid wood seats on pushpits
- Handrails in stainless steel to the front of deck house
- Stainless steel pulpit guard for air vents

#### COCKPIT CENTRAL

- Cockpit bottom self bailing
- Stainless steel and PMMA protective windscreen
- Cockpit surrounded by solid wood bulwark
- Cockpit benches and bottom decked in solid wood
- 1 Storage locker
- 2 Rope lockers
- Steering station to forward port in cockpit - Adjustable solid wood helmsman seat
- 1 Stainless steel steering wheel on partition - Diameter 800 - Leather-covered - Hydraulic steering gear on partition
- 1 Emergency tiller
- 1 Steering compass on binacle
- Engine control at steering station - Engine control panel facing steering station under windscreen
- Solid wood cockpit table - 2 flaps - Cool box - Protective PVC cover
- Space for navigation electronics (optional extra) facing steering station under windscreen
- 2 Waterproof loudspeakers
- Inwardly retractable companionway door and sliding companionway hatch in PMMA

#### AFT QUARTERDECK

- 1 Gas box locker to port aft
- 1 Rubbish locker to starboard aft
- 2 Large lockable lockers to port and starboard aft
- 1 Sliding and swinging gangway on aft swim deck - hydraulic-assisted opening (Patent Bénéteau) - Remote control - Solid wood decked
- 1 Life raft locker under gangway steps
- 1 Stainless steel swimming ladder - solid wood steps
- Shower hot / cold water

## FITTINGS

- Alpi woodwork in fruit tree colour matt varnish
- Parquet type matt-varnished floors
- Padded ceilings

## COMPANIONWAY

- Height to deck beam: 2.18 m
- Companionway steps with wood surround and non-slip surface
- 2 Wooden handrails fitted into companionway
- Oilskins cupboard to port

## SALOON

- 2 Fixed hull porthole(s) with blackout curtains
- 4 Opening portholes in coaming with blackout curtains
- 2 Opening deck hatches with roller blinds
- 1 3-section panoramic porthole with blinds
- Mast covered with wooden casing

## CHART TABLE TO STARBOARD

- Height to deck beam: 2.18 m
- Control console with flap - glove boxes - Storage - Moulded wood beading
- Wooden helmsman seat with moulded form - Storage locker
- Navigation instrument panel (without instruments)
- Radio CD player / Stereo MP3 - 2 Loud speakers
- Storage - Drawers - glove boxes

## PORT SALOON

- Height to deck beam: 1.98 m
- Dished bench seat with triple thickness foam seating / double thickness foam backrest
- 4 Matching decorative cushions
- Storage space behind and under bench seat
- Foldaway saloon table convertible to cocktail table - Varnished wooden top, inlay and laminar wood - Central leg
- Cupboard - Closed cubbyholes - Stainless steel and wood beading
- 2 Removable folding moulded wood seats and cushion

## STARBOARD SALOON

- Height to deck beam: 1.98 m
- 1 2-seater bench with central armrest
- Shelf / Sideboard removable (Storage under bench)
- Closed cubbyholes

## GALLEY

- Height to deck beam: 2.18 m
- U-shaped kitchen
- Synthetic resin worktop
- Closed cubbyholes and storage cupboards
- 1 Stainless steel sink 2 rectangular basins
- Gas cooker - 3 hob Oven Grill Stainless steel, mounted on gimbals - safety bar
- Electric extractor hood
- 1 Fridge in stainless steel - 130 l - front opening
- 1 Cold storer - 150 l - top opening
- 1 Fixed hull porthole(s)
- 2 Opening portholes in coaming
- 2 Opening cockpit porthole

## FORWARD CABINS

- Height to deck beam: 1.97 m
- 2 Symmetrical cabins each one consisting of:
  - Double bed (2,02 x 0,84 x 1,86) - Double thickness marine mattress (treated anti mite, fungicidal, bacteriacidal, allergenic)
  - Drawers - Hanging locker
  - 1 Fixed hull porthole(s) with blackout curtains
  - 2 Opening deck hatches with roller blinds

## FORE WASHROOM

- Height to deck beam: 1.94 m
- 2 Private toilet closet each with:
  - Glass bowl top, fitted washbasin - Mixer tap hot / cold water
  - Large size marine toilet - Seat
  - Storage
  - Mirrors
  - Toilet accessories: Glass holder, soap tray, towel rail, Rubbish bin, Paper dispenser
- 1 Shower compartment reached through the 2 toilet closets, with:
  - Compound monobloc casting washroom
  - 2 Frosted PMMA shower panel
  - shower mixer tap hot / cold water
  - 1 Opening deck hatch with roller blind

## PASSAGEWAY

- Engine compartment access door
- Electrics panel
- Panel for installing optional extra controls (e.g.: Air conditioning - Heating - Generator)
- 2 Opening cockpit porthole

## WASHROOMS PASSAGEWAY

- Compound monobloc casting washroom
- Glass bowl top, fitted washbasin - Mixer tap / Shower hot / cold water
- Large size marine toilet - Seat
- Mirrors
- 1 Rigid sewage tank (50 litres)
- Storage
- Toilet accessories: Glass holder, soap tray, towel rail, Rubbish bin, Paper dispenser
- 1 Opening portholes in coaming with roller blind

## STARBOARD WALKWAY CABIN

- 1 Single bed (1,95 x 0,51 x 0,63) - Marine mattress
- Drawers - 2 Cupboards - shelves glove boxes
- 1 Opening portholes in coaming with blackout curtains
- 1 Fixed hull porthole(s) with blackout curtains

## OWNER'S AFT CABIN

- Height to deck beam: 2.13 m
- Double bed island bed (2,00 x 1,30 x 1,80) - Lathed bed base - Double thickness marine mattress (treated anti mite, fungicidal, bacteriacidal, allergenic) - Padded bedstead
- 2 Bedside tables
- Drawers - glove boxes - Closed cubbyholes - Wardrobe - Shelves with wood beading
- Desk / Dressing table
- Sideboard bench seat
- 2 Fixed hull porthole(s) with blackout curtains
- 2 Porthole(s) opening on aft quarterdeck with blackout curtains
- 1 Opening portholes in coaming with blackout curtains
- 2 Opening deck hatches with roller blinds

## WASHROOM OWNER'S

- Height to deck beam: 2.00 m
- Separate shower - Compound monobloc casting washroom - Shower guard PMMA - shower mixer tap hot / cold water
- Glass bowl top, fitted washbasin - Mixer tap hot / cold water
- Large size electric marine toilet - Seat
- Storage
- Mirrors
- Toilet accessories: Glass holder, soap tray, towel rail, Rubbish bin, Paper dispenser
- 1 Opening portholes in coaming with roller blind

## ENGINE

- YANMAR 160 HP Diesel
- Engine chassis integrated into counter moulding hull structure - Engine fixed with elastic suspension
- Engine compartment: under central cockpit - Soundproofing foam
- Engine control - Key ignition - Control panel (Lighting, Ignition key, Rev counter, Hour meter, Oil pressure gauge, Water temperature indicator and warning, oil pressure and charge warning, diesel gauge) at steering station
- 1 ALTERNATOR 12V: 80 Amperes
- 1 ALTERNATOR 24V: 55 Amperes
- 2 Rotation moulded diesel tanks (total 480 l - Aft cabin(s)) - 1 Deck filler in stainless steel - Interconnecting valve system - Gauges
- Filters: Sea water - Diesel - Decanter
- Stainless steel propeller shaft (40mm diameter) mounted in polyester hull heel
- 3 -blade propeller Max Prop
- 1 Engine access door in walkway - Access through companionway fitted with hinges and gas pistons - Access through cockpit bottom for «major work»

## ELECTRICITY

- 12V and 24V circuit
- 220 V circuit
- Ducts for cables
- Ducts with messenger lines for threading cables of electrics or navigation electronics optional extras

### 12V AND 24V CIRCUIT

- Equipment on 12V: Radio CD player/MP3 - Electronics (optional extra)
- Equipment on 24V: Electric windlass - Bow thruster - Pumps - Navigation lights - Lighting - Fridge / Cold storer
- 1 Engine start 12V battery, 140 Amp
- 1 Service 24V battery set, 280 Amp (4 x Batteries 12 V 140 Amp)
- Battery switch
- 1 Battery charger 20 Amp 12 V
- 1 Battery charger 40 Amp 24 V
- Charge divider 120 Amp
- 1 ALTERNATOR 12 V: 80 Amp
- 1 ALTERNATOR 24 V: 55 Amp
- Electrical panel 12 / 24 V - 25 Functions - Voltmeter, Ammeter, Circuit breakers, Test batteries, Panel lighting, Water gauge
- Chart table 12V socket - Cockpit 12V socket

### 220 V CIRCUIT

- Equipment on 220V: Cabin sockets (1 in each cabin, 1 at chart table, 2 in kitchen, 2 in saloon) - Water heater - 2 Battery chargers - Microwave oven (Options) - Dishwasher (Options)
- Shore power socket 220 V - protected by differential circuit breaker - linked to distribution switchboard
- Electric 220V control panel

### LIGHTING

#### 24 V circuit

- Low consumption halogen ceiling lights in cabins, saloon and kitchen with separate switches
- Fluorescent ceiling lights in toilet closet
- Courtesy lights in saloon
- Shade lamps in saloon and master cabins
- Ceiling light in engine compartment
- Reading lights in cabins
- Automatic lighting in hanger closets

### NAVIGATION LIGHTS / DECK

- 1 Port/starboard prow light on pulpit
- 1 Sternlight on pushpit
- 1 Steaming light
- 1 Mooring light on masthead
- 1 Deck searchlight

### PLUMBING

- 4 Polyester freshwater tanks (1000 litres in the saloon) - 2 Stainless steel deck water fillers - Vents - Interconnecting valve system - Gauges
- Pressurised electric water pump - Expansion chamber - System protection filter
- Water heater 42 litres (Operation off engine or on 110/220 V electrical system)
- 1 Rigid sewage tank (50l) in walkway toilet
- Automatic electric shower drain pumps
- 1 Manual bilge pump - 1 Electric bilge pump - 1 Electric bilge pumps with automatic start mechanism
- 1 Electric ice box drain pump

### GAS

- Gas box in port aft locker - Space for 2 bottles (no bottle)
- Supply system in copper
- Pressure reducing valve and safety tap

## SERIES PREMIUM

	<b>PREMIUM*</b>
Steel blue colour hull - White and Gold hull decoration	■
Catwalks decked in natural solid wood	■
2 Stainless steel mast foot pulpits	■
Windlass control in cockpit with chain counter	■
Speakers Bose Acoustimass® 3 Black in the saloon	■
Microwave oven 220 V	■
Dishwasher 220 V	■
Bunk berths in the walkway cabin	■
2 Additional service batteries 140 amperes 24 V	■
Shore freshwater supply	■
Seawater deck wash in chain locker	■
12V refrigerator unit in cockpit table	■
Washing machine - Tumble dryer 220 V	■
Additional 185l diesel tank	■
Generator 9.5 KVA 220 V / 50 Hz - with casing	■
Pack Electronic RAYMARINE	■

### DESCRIPTION PACK ELECTRONIC RAYMARINE

#### Steering wheel on partition

##### Instrument console:

- ST 290 Data repeater screen
- Graphic displays ST 290
- Analogue anemometer wind indicator ST 290
- Analogue tiller angle indicator ST 290
- Multifunction screen E80 LCD colour 8,4" (GPS - tracker - Cartography chart mapper Navionics Gold, supplied without chart), Radar function
- Secondary VHF receiver, Loudspeaker RAY 240 E
- Automatic pilot with control console ST 290, LS RV2

##### Chart table:

- Graphic displays ST 290
- VHF DSC , Loudspeaker RAY 240 E
- Remote pilot control, Wireless instruments repeater Smartcontroller
- PC interface

- Radome aerial for radar function
- Gyro compass sensor

#### Steering wheel on column (optional extra)

##### Instrument console:

- ST 290 Data repeater screen
- Analogue anemometer wind indicator ST 290
- Analogue tiller angle indicator ST 290
- Multifunction screen E80 LCD colour 8,4" (GPS - tracker - Cartography chart mapper Navionics Gold, supplied without chart), Radar function
- Secondary VHF receiver, Loudspeaker RAY 240 E

##### Steering wheel console:

- Automatic pilot with control console ST 290, LS RV2
- Offset digital keyboard ST 290 for graphic screen control + Data
- Graphic displays ST 290

##### Chart table:

- Graphic displays ST 290
- VHF DSC , Loudspeaker RAY 240 E
- Remote pilot control, Wireless instruments repeater Smartcontroller
- PC interface

- Radome aerial for radar function
- Gyro compass sensor

\* Additional equipment available on special Premium

## OPTIONS

---

- Receiver AIS Raymarine
- 2 nd Multifunction colour screen Raymarine E 80 or E 120 at the chart table
  
- Steering wheel on column
- Manual or electric anodised mast furling system (without sail)
- Electric genoa furling system (without sail)
- Cruise sails for standard mast (Genoa 140% on furling with anti-UV protection strip - Standard bearing traveller mainsail, 3 Reef bands, Full batten)
- Cruise sails for furling mast (Genoa 140% on furling with anti-UV protection strip - Furling mainsail)
- Releasable fore-stay chain-plate + Sail tack
- Manual or electric fore stay sail furling system (without sail)
- Fore stay sail for furling
- Asymmetric spinnaker rigging (1 Halyard winch 46.2 STC HARKEN on mast - 1 Halyard - 1 Boom lift - 2 Spinnaker sheets - Blocks - Clutches)
- Symmetrical spinnaker rigging (1 Halyard winch 46.2 STC HARKEN on mast - 1 Halyard - 1 Boom lift - 2 Sheets and 2 spinnaker arms - Blocks - Clutches)
- Anodised spinnaker pole with storage on mast and trim track on front of mast
- Port electric rigging winch H46.2 STCEH (In replacement of standard)
- Electric genoa sheet winches H77.2 STCEH (In replacement of standard)
- 2 Spinnaker sheet winches H53.2 STC
- Electric davits 300 kg Bezenzoni
- Loading mast in boom
- Wood and aluminium gangway
- Deck house and cockpit surround decked in solid wood
- 2 or 3 hooped blue captain deck house hood
- Blue captain sun awning
- Blue captain bimini top
- Bleu captain cockpit cushions
- Blue captain sun mattress
- 3 blade propeller Gori
- Emergency rope cutter
  
- Water maker (24 / 220 V - 60 l/h)
- Air conditioning
- Heating
- Ice maker
- Additional electric toilets
- Additional rigid toilet reserves
- Safe
- mosquito nets
- 20" LCD TV in saloon or aft cabin - TV aerial - Player DVD / CD / MP3